

FICHA TÉCNICA DE EQUIPOS

HUAWEI - EchoLife EG8141A5:



Dimensiones	30 mm x 152 mm x 105 mm
Peso	< 180 g
Temperatura de operacion	0°C to +40°C
Humedad en operacion	5% RH to 95% RH
Entrada de energia	100V to 240V AC, 50/60 Hz
Adaptador de corriente	11V to 14V DC, 1.5A
Consumo de energía estatico	3.1W
Maximo consumo de energia	7.15W
NNI	GPON
UNI	1 POTS + 1 GE + 3 FE + 2.4G Wi-Fi
Conector optico	SC/APC
Indicadores	POWER/PON/LOS/LAN/TEL/WLAN/WPS

TP-LINK – TL-WR850N:



Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Boton	WPS/RESET Button
Adaptador de corriente	9VDC / 0.6A
WIFI	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensiones	182 x 128 x 35 mm
Antena	2 Antenas
Frecuencia	2.4-2.4835GHz
Transmisión de señal	11n: Up to 300Mbps 11g: Up to 54Mbps 11b: Up to 11Mbps
Transmision de energía	CE: <20dBm FCC: <30dBm
Funciones inalámbricas	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
DHCP	Server, Client, DHCP Client List, Address Reservation
Seguridad inalámbrica	64/128-bit WEP, WPA / WPA2,WPA-PSK / WPA2-PSK
Calidad de servicio	WMM, Bandwidth Control
WAN	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP
Administracion	Access Control Local Management Remote Management Agile Config (Optional)
Port Forwarding	Virtual Server,Port Triggering, UPnP, DMZ
DNS Dinamico	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Control de acceso	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall – Seguridad	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Protocolos	Support IPv4 and IPv6
Red de invitados	2.4GHz Guest Network x1